

Model		NovoDisplay DK430	NovoDisplay DK550	NovoDisplay DK650	NovoDisplay DK750
DISPLAY	Technologie	IPS Panel, Backlit LED	IPS Panel, Backlit LED	IPS Panel, Backlit LED	IPS Panel, Backlit LED
	Diagonale	43"	55"	65"	75"
	Helligkeit	350 Nits			450 Nits
	Native Auflösung	4K-UHD (3840 x 2160)			
	Seitenverhältnis	16:9			
	Kontrast	1,300:1			
	Betrachtungswinkel (horizontal/vertikal)	178°/178°			
	Bildwiederholrate (Hz)	60 Hz			
	Farben	1.07 Billions			
	Ausrichtung	Landscape			
SYSTEM	Betriebssystem	Android™ v7.1			
	CPU	RK3399 ARM Cortex A72 and Quad Core ARM Cortex A53			
	GPU	Mali™- T860MP4			
	RAM	2GB DDR3			
	Interner Speicher	16GB (eMMC Flash)			
KONNEKTIVITÄT	BYOD-unterstütztes System	Windows 7 / 8 / 10 (32 bits and 64 bits), macOS 10.7 and above, Ubuntu, iOS 7.0 and above, Android 4.0 and above, Chromebook			
	Eingang	HDMI v2.0 (x2), DisplayPort v1.2 (x1), DVI-D (x1), VGA (x1), Audio-In Mini-Jack 3.5mm (x1), USB A 2.0 (x3), USB C (x1), microSD Slot, RS232 (x2)			
	Ausgabe	DVI-D (x1), Audio-Out Mini-Jack 3.5mm (x2), RS232 (x1)			
	Netzwerk	LAN (x1), Wifi 802.11ac,b/g/n 2.4GHz & 5GHz			
FEATURES	Zusammenarbeit	BYOD Wireless Screen Mirroring, Meeting ID, Customizable Meeting Room Name, QR Code Connection Support, Split Screen, Moderator, Customizable Welcome Screen, USB Multimedia Reader			
	Digital Signage Infotafel	NovoDS Digital Signage - Message and Annocement Board, Intuitive Drag-and-Drop Interface, Flexible Playlist Creation, Dynamic Content from text, audio, photos and videos to webpages, Twitter, RSS, Google Calendar, Weather, and More			
ALLGEMEIN	Interne Lautsprecher	5W (x2) (Stereo)	5W (x2) (Stereo)	8W (x2) (Stereo)	15W (x2) (Stereo)
	Netzteil	Supply: AC 100-240V, 50/60Hz. Consumption: 85W, <0.5W (Standby)	Supply: AC 100-240V, 50/60Hz. Consumption: 140W, <0.5W (Standby)	Supply: AC 100-240V, 50/60Hz. Consumption: 170W, <0.5W (Standby)	Supply: AC 100-240V, 50/60Hz. Consumption: 400W, <0.5W (Standby)
	Betriebsumgebung	Operating Temperature: 0°C - 40°C. Operating Humidity: 20% - 85% (No Condensation)			
	Lagerumgebung	Storage Temperature: -10°C - 60°C. Storage Humidity: 10% - 90% (No Condensation)			
	VESA	VESA 400 x 200	VESA 400 x 400	VESA 600 x 400	VESA 600 x 400
	Produktabmessungen (T x H x B)	970 x 559 x 85 mm	1,244 x 714 x 70 mm	1,477 x 852 x 80 mm	1,715 x 993 x 93 mm
	Breite der Blende (U/B/L/R)	13 mm	13,9 mm	23,1 mm	31,5 mm
	Gewicht (netto)	9 Kg	15 Kg	29 Kg	41 Kg
	Lieferumfang	Flat Panel, OPS Module, Antennas, Wall Mount Kit, AC Power Cord, Remote Control with Batteries, Document Kit			
	Optionales Zubehör	LauncherPlus Type A, LauncherPlus Type C, LauncherOne			
LOGISTIK	Gewicht (Brutto)	13 Kg	19 Kg	40 Kg	53 Kg
	Kartonabmessungen (T x B x H)	1,070 x 153 x 633 mm	1,364 x 154 x 824 mm	1,660 x 245 x 1,045 mm	1,880 x 245 x 1,125 mm
	UPC	813097024657	813097024664	813097024671	813097024688